

Blinking LED Lamps

TYPE NO.	SOURCE COLOUR	λ_p (nm)	IV MIN (mcd)	VF (V)	OPERATING VOLTAGE (V)	PULSE RATE (Hz)	VIEWING ANGLE 20 1/2 (degree)	PACKAGE	CASE
				[IF=20mA]					
MOGB517W	Orange	630	10	5 [IF=20mA]	2	0.8~1.9	70°	T-1 1/4 Standard φ 5.0mm Orange Blinking Green Continuous Light	L-517d
	Green	565	10						
MSB557TA	GaAlAs Red	660	300	3	1.6~3.5	0.6~1.8	20	T-1 1/4 Standard φ 5.0mm	L-51b
MSB557TA-Hz2	GaAlAs Red	660	300	3	1.6~3.5	1.8~3.4			
MOB557TA	Orange	630	130	3	1.6~3.5	0.6~1.8			
MSB557DA	GaAlAs Red	660	50	3	1.6~3.5	0.6~1.8	40		
MOB557D	Orange	630	60	3	1.6~3.5	0.6~1.8			
MOB557DR	Orange	640	60	3	1.6~3.5	0.6~1.8			
MGB557D	Green	570	35	3	1.6~3.5	0.6~1.8			
MSB558DA	GaAlAs Red	660	35	3	1.6~3.5	0.6~1.8	66	φ 12mm 1" Lead	L-120b
MSB559TA	GaAlAs Red	660	3000	3	1.6~3.5	0.6~1.8	16	φ 10mm Bomb Type	L-90b